

Codice: 6D6414

Star Teak detergente



CLEANER FOR TEAK WOOD

Alkaline based concentrated detergent solution for the cleaning of teak decks of boats and for other untreated surfaces onboard. Removes the ingrained dirt, restoring the original wood colour. STAR TEAK CLEANER is part of the Star Teak Line, also including Star Teak Brightener and Star Teak Sealer.

Technical Characteristics

Paint Type	degreaser
Binder type A	Alcaline
Specific gravity kg/lit (±0,05)	1,067
Shelf life (+10+30°C)	18 months in airtight cans

Application Data

Application	Brush
Brush-Roller	Dilution with 3 or more pieces of fresh water
Relevant humidity	Less than 80%

SURFACE PREPARATION AND APPLICATION


TEAK WOOD.

Wet the wood surface with fresh water and apply STAR TEAK CLEANER evenly all over the surface, diluted with 3 or more parts of water. Let it stand for few seconds, then brush vigorously the surface and finally rinse with plenty of fresh water. (Do not use metal wirebrushes since their particles could stain wood by oxidation).

Note. In case after the cleaning procedure it should be necessary to brighten the colour of wood or remove any grey or blackish shade caused by ageing, then use STAR TEAK BRIGHTENER.

NB: This product is part of the Skipper's Line of Marine Coatings. For further application details please also see the "Indicative Coating Systems information" available on demand for Wood, Steel, Aluminium and Fibreglass boats. When in doubt contact for advise.

Colors



Colore: INCOLORE
Cod. Colore: 6D6414

Codice: 6D6414

Star Teak detergente

Listino

Formati Disponibili	Codice	Descrizione	Confezione
1L	6D641401000	Star Teak Detergente (Cleaner)	1.00 lt

SAFETY PRECAUTIONS

Before starting paint application attention should be paid to the symbols of risk specified on the label of each can. Please carefully read all the safety precautions advised on the label, or in the safety data sheet available on request at laboratorio@aemmecolori.it

NOTES

This information is provided to the best of our current knowledge, however, because the conditions of use of our products are beyond our control, this information does not constitute any kind of implied warranties; in that sense the supplying company accepts from now responsibility that can be connected to an abnormal use of the products. The Engineering Department at your location is available for any questions related to the use of our products. The percentages of dilution and the drying time are to be considered only indicative, in relation to a temperature of 20 ° C and are therefore subject to change with the change of temperature, in the presence of particular weather conditions or application determining factors at the time of application.